TRAXTER®

PNEUMATIC SKID STEER TYRES

Thick Reinforced Sidewall for puncture protection

Heavy Duty Tread Compound for all round service

High Traction Lug for superior grip

Extra Deep Tread for long life

Rim Guard to protect wheels against kerb damage

Size	Pattern	Ply Rating	Type	Rec Rim Width	Tread Depth (mm)	Unloaded Inflated Dimensions (mm)		Max Load Capacity		Max Inflation (kPa)
						OD ±2%	SW ±2%	kg	lbs	
10-16.5	R4	8	Tubeless	8.25	18.0	776	264	1875	4150	410.0
10-16.5	R4	10	Tubeless	8.25	18.0	776	264	2140	4700	510.0
10-16.5	L5	12	Tubeless	8.25	35.0	798	259	2180	4790	410.0
12-16.5	R4	10	Tubeless	9.75	21.0	840	320	2540	5600	450.0
12-16.5	R4	12	Tubeless	9.75	21.0	840	320	2890	6350	560.0
12-16.5	L5	12	Tubeless	9.75	36.0	838	307	2575	5665	450.0
12.5/80-18	I3	12	Tubeless	9.00	26.5	992	310	3150	6930	510.0

All Tyres conform to ETRTO and T&RA standards

For your requirements please contact -

TRIDENT INTERNATIONAL PVT. LTD.

Survey No. 70/A, Rashmi Industrial Estate, Wanawadi, Pune - 411040, INDIA
Phone : +91-20-71199100 **Fax :** +91-20-71199199
E-mail : exports@trident-intl.com ; sales@trident-intl.com
Website : www.trident-intl.com

creative@zowares.com